# The Dynamic Duo

Introducing the Titan ATF 4400 and ATF 6400 Automatic Transmission Fluids





**TITAN ATF 4400 Ultra High Performance ATF specifically** formulated for Japanese passenger and light commercial vehicles as well as transmissions used by several **European and American** manufacturers.

Although TITAN ATF 4400 has been designed for AISIN WARNER automatic-transmissions used in a large number of passenger and light duty vehicles of Japanese make, it is also suitable for use in a large selection of American and European models.

Due to its outstanding properties TITAN ATF 4400 can also be used in many aggregates of Asian origin or where DEXRON III-type fluids are demanded.

And as TITAN ATF 4400 (part number: 4935) has been totally updated - and replaces the old TITAN ATF 4400 (part number: 3970) – special effort should be made to ensure this product is used within the correct vehicles.



**UPDATED** 

# JASO M315 TYPE 1A

**SPECIFICATIONS** 

**APPROVALS** N/A

# RECOMMENDATIONS

- BMW MINI 83 22 0 402 413/83 22 7 542 290 CHRYSLER MS7176E/9602 (ATF +3/+4)
- DAIHATSU ALUMIX ATF MULTI
- **DEXRON III**
- FIAT 9.55550-AV1/AV4
- FORD M2C924-A/M2C922-A1
- FORD MERCON
- GM 9986195
- HONDA ATF Z-I
- HYUNDAI SP III
- ISUZU BESCO ATF-II/ATF-III JATCO 3100 PL085/FWD (N402)/JF506E (K17)
- JWS 3309/TYPE T-IV
- MAZDA ATF D-III/ATF M-3/M-V
- MITSUBISHI SP-II/-III
- NISSAN MATIC C/D/J
- **SAAB 3309**
- SUBARU ATF OIL/ATF OIL SPECIAL/ATF HP
- SUZUKI ATF 3309/3317
- TOYOTA TYPE D-2/T/T-II/T-III/T-IV
- VW G 052 990/055 025

# PACK SIZES

1L | 4L | 20L | 60L | 205



**TITAN ATF 6400 is a Premium** Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. In addition, it is also licensed according to **DEXRON VI and MERCON LV.** 

TITAN ATF 6400 has been specially designed to deliver performance and increased fuel efficiency for modern automatic transmissions of Japanese and American manufacturers where reduced viscosity is required and meets the stringent DEXRON-VI and MERCON LV specifications.

Along with providing exceptional anti-shudder performance and consistent and strong friction control properties, TITAN ATF 6400 is also supported by real-world testing conducted from 1 million kilometres.

And as DEXRON VI is strictly backwards compatible in GM applications, TITAN ATF 6400 can also be used in older GM automatic transmissions.

4L

### **SPECIFICATIONS**

JASO M315 TYPE 1A-LV

Automatic Transmission Fluid

# **APPROVALS**

- DEXRON® VI
- FORD MERCON LV
- ZF TE-ML 09

# **RECOMMENDATIONS**

- AISIN WARNER/AW-1 BMW 81 22 9 400 272
- BMW 81 22 9 400 275
- BMW 81 22 9 407 738
- BMW 83 22 0 397 114
- BMW 83 22 0 403 248
- BMW 83 22 0 403 249 BMW 83 22 0 432 807
- BMW 83 22 2 167 718
- BMW 83 22 9 407 858
- BMW 83 22 9 407 859
- FIAT 9.55550-AV2
- GM 9256039/88863400 HONDA DW-1
- HYUNDAI SP IV
- **HYUNDAI NWS 9638**
- JWS 3324
- KIA SP-IV
- MITSUBISHI DIA QUEEN ATF-MA1
- NISSAN MATIC S
- TOYOTA TYPE WS
- VW G 055 540 A2

### PACK SIZES

4L | 20L | 205



An ultra-high performance automatic transmission fluid, TITAN ATF 6006 has been specially developed to optimise the shifting performance of selected ZF automatic transmissions.

In addition, TITAN ATF 6006 features a reduced viscosity to optimise the performance of specific 6-speed ZF automatic transmissions.

Along with delivering good friction control, TITAN ATF 6006 also features excellent durability and oxidation control which provides long oil life with proven performance across a wide range of vehicles.

PART NO.

4909

### **SPECIFICATIONS**

# APPROVALS • N/A

- IV/A
- RECOMMENDATIONS
- AML Oil No. 4G4319A509/AA/S
- BENTLEY PY112995PA
- BMW 83 22 0 142 516
- BMW 83 22 2 305 396
- HYUNDAI 040000C90SGJAGUAR FLUID 8432
- LAND ROVER TYK500050
- MASERATI 231603
- VW G 055 005

### PACK SIZES

20L

A premium performance automatic transmission fluid, TITAN ATF 6008 has been specially developed to optimise the shifting performance of selected ZF automatic transmissions.

In addition, TITAN ATF 6008 features a reduced viscosity to optimise the performance of specific 6 as well as 8-speed ZF automatic transmissions.

Along with its strong antishudder performance, improved friction control, excellent oxidation performance and wear protection, TITAN ATF 6008 has also been created for usage across a diverse range of range of vehicles. PART NO.

4910

# SPECIFICATIONS N/A

. . . .

# **APPROVALS**

N/A

# RECOMMENDATIONS

- BMW 83 22 2 289 720 (ATF 3+)
- CHRYSLER 68157995AA
- FIAT 9.55550-AV5
- JAGUAR 02JDE 26444
- LAND ROVER LR023288
- VW G 055 162
- VW G 060 162

# PACK SIZES

20L



# **Customer Support at your fingertips**

The world of automotive lubricants is complex and fast-paced. The Fuchs Netlube Oil Selector app will provide all of information you need, whenever and wherever you need it.

Download the app to your smartdevice today by searching Fuchs Netlube in the app store.





# **FUCHS LUBRICANTS AUSTRALASIA**

# **Head Office Melbourne**

49 McIntyre Road, Sunshine Victoria 3020 Phone: 1800 1800 13 Fax: 1800 1800 14 Email: customer.service@fuchs.com.au

fuchs.com.au

# **New Zealand Office**

485c Rosebank Road, Avondale, Auckland 1026 Phone: 0800 382 476 Fax: 09 820 3643 Email: customer.service@fuchs.com.au

fuchs.co.nz

LUBRICANTS.
TECHNOLOGY.
PEOPLE.



This brochure is accurate in information to the Fuchs Lubricants product range at the time of printing. Fuchs Lubricants reserves the right to make changes at any time without notice. Details also available from your Fuchs Lubricants representative. Copyright FUCHS Lubricants (Australasia) Pty. Ltd. March 2020.